

LMD-800 SERIES





Features

- Digital signal processor
- Auto white balance
- Automatic gain control
- Auto backlight compensation
- Water proof, antivandal dome camera: IP64
- Built in 4mm~9mm Auto diaphragm lens selectable(optional)
- LED built in (optional)
- Light Sensor driver RoHS



Dimensions



ITEMS	LMD-800 SERIES
SCANNING SYSTEM	2:1 Interlace
ELECTRONIC SHUTTER	Auto
GAIN CONTROL	Auto
BACK LIGHT COMPENSATION	Auto
WHITE BALANCE	Auto
WEATHER PROOF IP RATING	IP 64
S/N RATIO	More Than 50 dB
GAMMA	0.45
VIDEO OUTPUT	1 VP-P, 75 ohms
STORAGE/OPERATING TEMPERATURE	-30°C ~ +60°C / -10°C ~ +45°C
DIMENSIONS (Ø×H) mm	Ø139×H:95
WEIGHT	700g

Model NO.	Image Sensor	PICTURE ELEMENTS H*V	TVL	Lens Type	IR	Power Consumption	Sensitivity F:1.2	Chip
LMD-800ASE	1/3" SONY CCD	NTSC:512(H)×492(V) PAL:500(H)×582(V)	420	3.6 mm		DC12V/80mA	0.1 LUX	NEXT CHIP
LMD-800ASR	1/3" SONY CCD	NTSC:512(H)×492(V) PAL:500(H)×582(V)	380	3.6 mm		DC12V/90mA	0.1 LUX	NEXT CHIP
LMD-800ASR/IR	1/3" SONY CCD	NTSC:512(H)×492(V) PAL:500(H)×582(V)	380	3.6 mm	•	IR ON DC12V/250mA	0.1 LUX	SONY 11R
LMD-800ASH	1/3" SONY Super HAD CCD	NTSC:768(H)×494(V) PAL:752(H)×582(V)	480	3.6 mm		DC12V/90mA	0.5 LUX	NEXT CHIP
LMD-800AXH	1/3" SONY Super HAD CCD	NTSC:768(H)×494(V) PAL:752(H)×582(V)	520	3.6 mm		DC12V/100mA	0.05 LUX	SONY 11X
LMD-800AXH/AI	1/3" SONY Super HAD CCD	NTSC:768(H)×494(V) PAL:752(H)×582(V)	520	4mm~9mm Autoiris		DC12V/120mA	0.05 LUX	SONY 11X
LMD-800AXH/AIR	1/3" SONY Super HAD CCD	NTSC:768(H)×494(V) PAL:752(H)×582(V)	520	4mm~9mm Autoiris	•	IR ON DC12V/270mA	0.05 LUX	SONY 11X