

LIS-01HA



Features

- Multi-profiles video, MPEG4&JEPG simultaneously dual encoders
- 3GPP mobile phone surveillance
- RJ45 for 10/100M network transmission
- 1 channel video in
- 1 channel audio in, 1 channel out
- RS485 for motor demo control
- External alarm Input/Output, build in motion detection
- Power over Ethernet option

ITEMS	LIS-01HA
Networking Protocols	TCP/IP, HTTP, SMTP, FTP, NTP, RTP ,RTSP, DNS, DHCP, UPnP, DDNS, PPPoE, DIPS
Connectivity	10//100 Mbps Fast Ethernet Auto negotiation
Video Encoders	Simultaneous dual encoders Enhanced video compression MPEG4 Simple Profiles& Motion JEPG
4 Video Profiles	MPEG4 30fps at 640x480 MPEG4 30fps at 320x240 MPEG4 30fps at 160x120 MJPEG 30fps at 320x240
Audio	G.726:16kbps~40kbps GSM-AMR 4.75kbps~12.2kbps RCA audio in Audio line out(for 2-way audio application)
Video input	BNC connector 75 ohm impedance Brightness/Contrast/Hue adjustable 50/60 Hz auto detection
Digital I/O &RS-485	DI*1/DO*1 RS485 for motor dome control
Security	2 layers: Administrator and User IP filter
Viewing System Requirement Protocol	Active X
Browser	Internet Explorer v6 or later
Web Management	Configuration accessible via a web browser Record or snapshots and save to local hard drive via Web browser
Motion Detection	4 areas motion detection Adjustable sensitivity and threshold bar Take snapshots to FTP or SMTP when motion triggered
Digital zoom	Adjustable digital zoom area No limit ratio
Power Input	12V DC, 1.5A adaptor B type Power over Ethernet(AM6121 only)