

Features



- The products imported by Japan SONY Exview HAD CCD
- Built in day and night dual-use, dual-filter switch function. True color during day, have more than 480TVL with the merits of ultra-high quality and ultra-minimum illumination
- Built-in 180X high efficiency of the fast-zoom
- The camera will automatically aim and follow the largest movement view, provide 360° panning, 90° tilting
- Have RS-485 control



LMS-2518 SERIES	
IMAGE SENSOR	1/4"COLOR CCD SONY EXVIEW HAD (Day and Night)
BISYNCHRONOUS	Internal synchronous
PIXELS	NTSC 410K Pixel PAL 470K Pixel
SENSITIVITY	0.1 Lux(Color),0.02 Lux(B/W) ,0 Lux IR illumination
LENS	18 x zoom lens 3.6~82.8mm(10 x Digital zoom)
S/N RATIO	50d/B(AGC OFF)
APERTURE CONTROL	Auto/Manual
IR FILTER CONTROL	Auto/Manual
FOCUS CONTROL	Auto/Manual
SHUTTER SPEED	NTSC:1/60~1/100,000 Sec. PAL:1/50~1/100,000 Sec.
VIDEO OUTPUT	1.0Vp-p ,75Ω
A REVISDE	0.45/1
AGC	Super AGC 0~36dB
WHITE BALANCE MODE	ATW 2500°~9500° Kpreset /Manual
WHITE BALANCE CONTROL	Auto on/off
RESOLUTIONS	480 TVL(Color)/600 TNL (B/W)
BLC	Super BLC/48 zone BLC
OSD	OSD menu
ROTATING WAY	Auto/Manual/Tour trace
RANGE (pan/ tilt)	Pan 0°~360°/ 0°~90°
ROTATIND SPEED	Level 100°/s Vertical 100°/s
SPEED SETTINGS	Auto5~60°/s /Manual 10~80°/s(automatic transmission depend on zoom ratio) / Alarm100°/s
DEFAULT STAY	0~64sec.
LENS CONTROL	180X
DI INPUT	2
DP INPUT	1
THE DEFAULT CONTROL	128
WAY OF CONTROL	RS-485
NUMBER OF CONTROL	ID 0-127
ASSOCIATE OF DEFAULT	-1°
POWER	DC 12V~ 13.5 V/ 1.0A
OPERATING TEMPERATURE/HUMIDITY	Temperature -5 °C~ -60 °C/ Humidity 10% ~90% RH
BAREBONES	Suctorial ,Sling ,hang (Indoor/Outdoor)
MATERIAL	Casement: Anti-Knock, strength anti-coating treatment Mount: High hardness 6061duralumin
COLOR	Casement: blister Mount: beige
DIMENSIONS (×H) mm	186×H1142 mm(7.3" ×h5.6")
WEIGHT	2.8kg