

LDR-04HA



LDR-08/16HA



Features

- H.264 high resolution data compression
720×480/720×576 D1 Recording
- Support 16 CH audio input 16CH alarm input
- Touch panel control
- Key lock function



Model No.		LDR-04HA	LDR-08HA	LDR-16HA
VIDEO SIGNAL	Television System	NTSC/PAL		
	Video Resolution	720×480(NTSC)/ 720×576(PAL)		
	Video Inputs	4 CH Cameras	8 CH Cameras	16 CH Cameras
	Video Input Signal	1.0 Vp-p 75Ohms		
	Video Outputs	Main monitor, Call monitor, VGA		
	Video Output Signal	1.0 Vp-p 75Ohms		
VIDEO FEATURES	Live (display FPS)	120(NTSC)/100(PAL)	240(NTSC)/200(PAL)	480(NTSC)/400(PAL)
	Zoom	2 times digital		
	Sequence	Sequence Display In Full Size		
	Display Format	Full screen, Quad spilt, 4 spilt	Full screen, Quad spilt, 9 spilt	Full screen, Quad spilt, 9 spilt, 16 spilt
	Video Enhance	Brightness, Contrast control each camera		
	VGA Enhance	Brightness, Contrast, saturation		
AUDIO	G.723	4ch Input/2ch Output	8ch Input/2ch Output	16ch Input/2ch Output
RECORD	Recording Speed(IPS)	120(NTSC)/100(PAL)	240(NTSC)/200(PAL)	240(NTSC)/200(PAL)
	Recording Resolution	720×480, 720×240, 360×240(NTSC)/ 720×576, 720×288, 360×288(PAL)		
	Codec	H.264		
	Recording	Timer, Motion, Alarm, Manual Individually Setting		
	Material	1SATA HDD	2 SATA HDD	
SEARCH	Timer, Motion	Fast ×32, Slow, Forward, Rewind, Image by image		
BACKUP	USB2.0	Each Camera, ALL Camera, Time range		
USER INTERFACE	Operating Interface	Mouse, IR Remote Control, Network	Mouse, Touch Panel Control, IR Remote Control, Network	
NETWORK	Ethernet 10/100M	PPPoE, TCP/IP, DHCP, DDNS Server		
ALARM	Alarm Inputs	4 Inputs	8 Inputs	16 Inputs
	Alarm latch up	1~10 sec		
	Buzzer Out	On/Off		
POWER	Input Voltage	DC 12V		
	Power consumption	Approx. 50W	Approx. 80W	
MECHANICAL	Dimension (m/m)	257(W)×217(D)×43(H)	335(W)×340(D)×52(H)	
	Weight(Kg)	Approx. 1.7 Kg	Approx. 3 Kg	
ENVIRONMENT	Operating Temperature	0~60deg C		
	Humidity	10~90%		